# DD666AM-D

**Dual/AM detector with 18 curtains of 20m, CO relay, VdS class-B certified**



# DD666AM-D

## Dual/AM detector with 18 curtains of 20m, CO relay, VdS class-B certified

## Spécifications techniques

### General

| | |
|---|---|
| Technology | Dual |
| Application type | Loftmontering |
| Anti masking | Yes |
| Pet immune | No |
| Camera | No |
| Pry-off tamper kit | ST400 (optional) |

### Detection

| | |
|---|---|
| Max. detection range | 20 m |
| Microwave frequency (nom.) | 5.8 GHz |
| Undercrawl protection | Yes |
| Alarm memory | Yes |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Kablede |

### Inputs/outputs

| | |
|---|---|
| Remote control lines | Tag/Nacht, Gehtest |

### Physical

| | |
|---|---|
| Mounting height | 2,5 bis 5 m |

### Environmental

| | |
|---|---|
| Environment | Indendør |

### Regulatory

| | |
|---|---|
| EN50131 grade | Lønklasse 3 |
| Certification | VdS |

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web fr.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57