ACT430E-5

(5 stk.) Mifare Classic S50 proxbrik med 7-byte UID (CSN)

Product overview

These Mifare Classic 1k keyfobs are to be used on ATS1160N/ATS1161N, ACI406/ACI407 and any other KGS Fire & Security Mifare or Transition reader supporting 7-byte Card Serial Numbers (CSN). The cards are unprogrammed and only the unique 7-byte ID-number of the Mifare® chip, the so called Chip or Card Identification Number (CSN) is used by the readers.



Detaljer

- Read only for CSN (7-byte)
- Read / Write function for card sectors

ACT430E-5

(5 stk.) Mifare Classic S50 proxbrik med 7-byte UID (CSN)

Tekniske specifikationer

System

Reading distance	0 to 10 cm
Memory size	1 kB
No. of Mifare bytes CSN	7 Bytes (S50)
Supported readers	ACI406/407 Mifare Readers, ATS1160/1161 Mifare Readers

Technology

Credential type	Nærhed
Credential operating frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN)

Ordering information

Cards/tags in package	1

Physical

Material	PA6
Form factor	Key Fob
Physical dimensions	45 x 30 x 14 mm
Net weight	16 g
Colour	Sort

Environmental

IP rating	IP66

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57