# EV669

**360° Ceiling Mount PIR Motion Sensor**



# EV669

## 360° Ceiling Mount PIR Motion Sensor

## Technische Spezifikationen

### General

| | |
|---|---|
| Technology | PIR |
| Application type | Loftmontering |
| Anti masking | No |
| Pet immune | No |
| Camera | No |
| Signal processing | 4D |
| Pry-off tamper kit | ST400 (optional) |

### Detection

| | |
|---|---|
| Max. detection range | 20 m |
| Undercrawl protection | No |
| Alarm memory | Yes |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Kablede |

### Inputs/outputs

| | |
|---|---|
| Remote control lines | Tag/Nacht, Gehtest |

### Electrical

| | |
|---|---|
| Power supply type | 12 VDC |

### Physical

| | |
|---|---|
| Colour | Hvid |
| Mounting height | 2,5 bis 5 m |

### Environmental

| | |
|---|---|
| Environment | Indendør |

### Regulatory

| | |
|---|---|
| EN50131 grade | Lønklasse 2 |
| Certification | NFA2P, VdS |



Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.