NC-DPO-B

Conventional optical smoke detector (Black)

General

The NC-DPO-B is a graphite black, photoelectric (optical) detector suitable for use in residential applications.

Application

The detector supports installation on the NC-DBR-B conventional detector base for standard stand alone applications. Detection sensitivities are programmable using the NC-D-PT device programmer.



Details

- Supports drift compensation to enable good environmental adaptability
- Self-diagnostic
- Local test activation with reed switch
- Chamber contamination checking
- All round LED visibility (360° viewing angle) avoids time spent on specific detector orientation
- Configurable blinking LED support
- Remote indicator output
- Removable sensing chamber for for easy maintenance
- 2 Programmable smoke sensitivity levels

NC-DPO-B

Conventional optical smoke detector (Black)

Technical specifications

General

Status indication	Red LED
User interface	Via LED - polling, fault, contamination and alarm
Compatibility	NC-Series conventional panels and Excellence series conventional zone monitors
Reset voltage	<1 VDC
Reset time	<10 s
Alarm levels	2
Connectivity	Zone connection - 2-core (polarity sensitive), RI connection - 2-core (polarity sensitive)

Electrical

Operating voltage	9.5 to 28 VDC (24 VDC typical)
Current consumption	<60 µA (Quiescent) ≤55 mA (Alarm)
Cable specification	>1.0 mm²
No. of cable cores	2
Terminals	4

Detection

Detection principle	Optical, tyndall effect
Sensitivity	Programmable
Zone length	Panel dependent

Output

Output quantity	1
Output type and rating	Remote indicator
Remote alarm output	Supported

Physical

Physical dimensions	54.5 mm (including base) x 100 mm Ø
Net weight	±110 g
Colour	Bianco (RAL 9016)
Mounting type	Loftmontering
Material (body)	ABS

Environmental


Vandal proof	No
Operating temperature	-10 to +50°C
Relative humidity	0 to 95% noncondensing
Environment	Indendør
IP rating	IP2x

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE

Compatible products

Category	Reference	Description
Detection device	NC-D-PT	Conventional hand held device programmer
Detection device	NC-DBR-B	Conventional relay base (Black)
Notification device	PA25/3L	Conventional remote indicator



KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 13:34