# SC-22-0200-0001-99

## SmartCell Dual Smoke/Heat Detector and Combined Sounder

### Overview

The SmartCell Dual Smoke / Heat Detector With Sounder is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include dual smoke and/or heat detection, integrated sounder with 32 tones, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



### Details

- Fully wireless
- Quick and easy to install
- Compact profile
- Flexible detection; smoke and/or heat
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

# SC-22-0200-0001-99

## SmartCell Dual Smoke/Heat Detector and Combined Sounder

## Technical specifications

### General

| | |
|---|---|
| Wireless frequency | 868 MHz |
| Compatibility | SmartCell, Excellence Gateway |

### Electrical

| | |
|---|---|
| Batteries | 3 x 3.6 V lithium thionyl chloride batteries.<br>Fanso: ER14505M<br>HCB: ER14505M (HCB-JS-TZ-02-547) |

### Sounder

| | |
|---|---|
| Output level | 89 dB(A) at 1 m max. |
| Output level adjustment | High or low |
| Selectable tones | 32 |

### Physical

| | |
|---|---|
| Physical dimensions | 110 x 58 mm (Ø x D) |
| Net weight | 0.2 kg |
| Colour | Hvid |
| Mounting type | Loftmontering |

### Environmental

| | |
|---|---|
| Operating temperature | -10 to +55°C |
| Storage temperature | -10 to +30°C (with batteries)<br>-10 to +55°C (without batteries |
| Relative humidity | 95% noncondensing max. |
| Environment | Indendør |
| IP rating | IP21C |

### Regulatory

| | |
|---|---|
| Compliancy | CE |
| Certification | CPR |
| Standards | EN54-3<br>EN54-5<br>EN54-7<br>EN54-13<br>EN54-25 |

### Detection

| | |
|---|---|
| Sensitivity | Smoke: Normal, Normal+AVF. Heat: 58 °C, static (A2S), 58 °C rate of rise (A2R), 72 °C static (BS), 72 °C rate of rise (BR) |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 26 May 2026 - 15:47