# PB521

**Arix set AIR, met 2 beams voor gebruik binnen max. 120 meter of gebruik buiten max. 60 meter.**



## Details

- Range 60/120 metres
- Indoor and outdoor installation
- 2 synchronised lines
- 4 optional frequency steps ensure that one receiver will only 'see' one transmitter
- Adjustable precision optics
- Immune to external light
- High protection against EMC noise
- AGC sensitivity control
- Extra lens heater available as an accessory
- Full range of tower accessories for outdoor fitting

# PB521

## Arix set AIR, met 2 beams voor gebruik binnen max. 120 meter of gebruik buiten max. 60 meter.

## Technische specificaties

### General

| | |
|---|---|
| Category | Aktive Infrarøde Stråler |
| Product type | Aktiv Infrarød Stråle |
| Infrared system | 2-beam LED, double frequency modulation |
| Tamper | NC (max. charge 30 VAC/VDC - 100 mA) |

### Detection

| | |
|---|---|
| Range | 60 / 120 m (outdoor / indoor) |
| Alarm response time | 50 to 700 ms |

### Inputs/outputs

| | |
|---|---|
| Alarm output | NC/NO (max. charge 30 VAC/VDC - 0.5 mA) |

### Electrical

| | |
|---|---|
| Power supply value | 12 to 30 VDC |
| Current consumption | 120 mA<br>85 mA |

### Physical

| | |
|---|---|
| Net weight | 380 g |
| Colour | Sort |
| Material | Polycarbonat |

### Environmental

| | |
|---|---|
| Operating temperature | -25 to +60°C |
| Environment | Udendørs |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57