# CDC4-EN

## Controlador inteligente de 4-8 puertas/ascensores con fuente de alimentación de 12V, 4 entradas Wiegand, EN50131

### Product overview

The CDC4-EN is a 4-8 door & lift controller. It provides for a complete and versatile access control solution to extend the Advisor Advanced and Axon system with advanced access control functions. It provides a complete integrated real-time alarm and access control system for four up to eight doors or lifts, with power supply and housing. A total of 12 door/lift controllers can be connected to an Advisor Advanced or Axon panel providing for a total of 48 up to 96 full access doors. The CDC4-EN door/lift controller can operate off-line with no degradation in performances, should communication with the Advisor Advanced panel fail as it offers full offline operation. This combined intrusion and access solution reduces wiring and required devices as the same devices like readers and inputs can be used for both purposes. Being EN50131 and NFa2p approved the inputs and power supply for door contacts and detectors can be used as part of an approved intrusion system.
Door and lift control can be used in one single door controller by configuring doors to lifts.


The CDC4-EN provides for the same size and connector arrangement as the ATS1250, including 4 Wiegand interfaces. This provides the most cost effective and easiest method to upgrade an older ATS1250 in an Advisor Advanced system, or when upgrading and ATS Master with ATS1250's to a current system where the ATS Master is replaced by Advisor Advanced or Axon panel.

### Expanders

Expanders are used to expand the number of alarm inputs in an Advisor Advanced and Axon system. Expanders allow inputs and outputs/relays to be connected at a location remote from an Advisor Advanced or Axon panel. Expanders communicate via poll & reply messages. Detectors, door contacts and other detection devices are connected to expanders that report any change of state to the control panel for processing. Available expanders include support for conventional devices, wireless devices as well as intelligent addressable devices. A special expander is available providing expansion of four to eight intelligent doors or lifts.

### Special features

Besides standard intrusion and access control options, the solution offers special features that are only possible due to the true combination of both. These features vary from changing security on doors when the intrusion area has disarmed, locking doors when the intrusion area arms, preventing access based on the intrusion area status or starting automatic arming when the last user has left an access control region. Special access control features include High Secure users for high secure areas like vaults, support for macro's to complement the standard features.
The lift functionality offers a solution where lift floor buttons can be controlled by access levels of users. Outputs referring to floors for that



### Detalles

- Alarma en tiempo real y control de accesos en 4-8 puertas/ascensores por controlador
- Certificado por EN50131-3, EN50131-6 y NFa2p para uso en sistemas de intrusión
- Base de datos completa para la operación fuera de línea
- Hasta 12 controladores CDC4-EN que proporcionan de 48 a 96 puertas inteligentes o ascensores
- Cualquier puerta se puede configurar como ascensor: use ambas juntas en un controlador
- Funciones completas de control de acceso: enclavamiento, recuento de usuarios, usuarios de alta seguridad, anti-passback con control regional.
- Hasta 65532 usuarios con tarjetas y/o PIN
- Hasta 32 lectores por CDC4-EN y 6 por puerta
- Dos buses de datos locales con protocolo configurable
- Soporta lectores Secure , lectores OSDP y cerraduras inalámbricas
- Entradas, 4 interface Wiegand, 4 relés de puerta, conexión IP y opciones de expansión, integradas en placa.
- Funcionamiento en modo extendido: usuarios de control de acceso gestionados por Advisor Management
- Anti-passback entre todos los controladores de puerta en modo estándar conectados a Advisor Advance o Axon

lift will switch to only allow press the button for the allowed floors.

## Security

The CDC4-EN has been designed with focus on security. Not only proving fully encrypted communication between the controller and management application, but also between the CDC4-EN controller and the Advisor Advanced or Axon panel, between the card and readers as well as between readers and the CDC4-EN controller or the Advisor Advanced or Axon panel. In other words, CDC4-EN provides communication security from card to software.

## Connectivity

Any CDC4-EN can operate in two modes. Depending the mode selected the CDC4-EN is controlled completely through the Advisor Advanced or Axon panel providing four doors or lifts per CDC4-EN which is named the standard mode. In standard mode the CDC4-EN behaves like legacy door controllers providing the same features and user data for the door controller and the Advisor Advanced or Axon panel.
In extended mode the CDC4-EN is also configured through the Advisor Advanced panel using the ATS8500 or ATS8550 downloader. Even in extended mode the CDC4-EN exchanges intrusion information with the Advanced panel. In extended mode however the CDC4-EN is also directly connected via IP to Advisor management for configuration of access and intrusion users while providing support of up to 8 doors or lifts per CDC4-EN. Advisor Management sends intrusion related user data to the Advisor Advanced panel and access related data directly to the CDC4-EN.
Extended mode is not yet supported on Axon control panels.

# CDC4-EN

## Controlador inteligente de 4-8 puertas/ascensores con fuente de alimentación de 12V, 4 entradas Wiegand, EN50131

## Especificaciones técnicas

### General

| | |
|---|---|
| Expander type | Tür controller |
| Product line | Advisor Advanced, Axon |
| Connection type | RS485 (a Advisor Advanced/Axon), IP (a Advisor Management) |
| Compatibility | Advisor Advanced, Axon (no Advisor Master) |
| Max. distance from panel | 1.5 km utilizando cable recomendado |
| Max. per panel | Hasta 12, dependiendo del tipo de panel |
| Specified cable | WCAT52 / WCAT54 o equivalente |

### System

| | |
|---|---|
| Users | Up to 65532 |
| PIN codes | Todos |
| Door groups | 128 a 50,000 |
| Timezones / holidays | 24 a 1000 |
| Addressing | Mikroprzełączniki |
| End-of-line resistor | Seleccionable |

### Inputs

| | |
|---|---|
| Total | 32 para intrusión |
| Onboard | 16 |
| Expandable | 16 para intrusión |

### Outputs

| | |
|---|---|
| Total | 16 para intrusión |
| Onboard | 4 |
| Expandable | 8 |
| Type of outputs | Reles / Colector abierto |
| Relays | 5 |
| Maximum number of outputs | 128 |
| Siren outputs | 1 |

### Backup

| | |
|---|---|
| Battery type | 7.2 - 36 Ah |
| Dynamic battery testing | Soportado |

### Electrical

| | |
|---|---|
| Power supply type | 230 VAC |
| Power supply value | 230 VAC +10%, -15%, 50 Hz |
| Power consumption | 3A a 13.8 VDC + 700 mA carga de bateria |
| Current consumption | 225 mA (incl Ethernet, sin reles activos) |
| Integrated power supply | Yes |

### Physical

| | |
|---|---|
| Physical dimensions | 465 x 480 x 160 mm |
| Colour | Beige |
| Material | Stahl (lackiert) |
| Housing | Metal |

### Environmental

| | |
|---|---|
| Operating temperature | 0 a +50°C |
| Storage temperature | -20 a +80°C |
| Relative humidity | 93% sin condensación |
| Environment | Drinnen |
| IP rating | IP31 |

### Regulatory

| | |
|---|---|
| Compliancy | CE |
| Certification | CE, EN50131 Grad 3 |

Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 12 November 2026 - 18:57