NC-PF2

Central de Incêndios Convencional, 2 zonas

Overview

The New Conventional fire control panels offer state of the art architecture in configurations that deliver an uncomplicated solution for small to mid-sized conventional applications. With their clean and attractive contemporary design, they fits with any decor. The basic and intuitive user interface with icons make easy their application everywhere without an additional language kit required.

With support for multiple lines of conventional detectors and accessories, these quick-to-configure systems offer versatility that benefits building owners and installation/maintenance companies alike.

The panel

The NC-PF2 is a conventional fire alarm control panel. It is supplied with 2 zones that support up to 32 devices per zone, as well as up to 2 supervised relay outputs dedicated to sounder control. In addition 2 conventional relay outputs dedicated to common fire and fault conditions, as well as two user configurable inputs for monitoring and control are available.

No Language Kit required for localization.

Options

The panels support 2 types of auxiliary relay boards, one with 4 standard relays, and one with 4 supervised relays. With these boards the panel outputs may be expanded with up to 8 additional outputs.

Approvals & Compliance

The product line carries the following accreditations:

• EN54:2, EN54:4 and CE approved
• CPD certified

• WEEE compliant
• RoHS compliant

Type class conditions: 3K5 of IEC 60721-3-3



Detalhes

- Design moderno e elegante com interface de utilizador básica e intuitiva com ícones.
- Componentes facilmente amovíveis para uma instalação rápida e simples.
- Modos de operação regionais.
- Suporta zona tipo Normal, remoção de dispositivo e intrínseco.
- Saídas supervisionadas de notificação.
- Relés de incêndio e de falha livres de potencial em conformidade com a norma EN54.
- Alteração de Classe, dia/noite e reset remoto
- Saída auxiliar de 24 VDC com possibilidade de reset.
- Compatibilidade por defeito com funções especiais, tais como: - níveis de acesso do utilizador em conformidade com a norma EN54 - zonas mistas - diagnóstico completo do painel frontal - walk teste um só utilizador - CleanMe™
- Placas de relé (opcionais) standard e supervisionadas.
- Funcionamento em rede até 64 zonas.
- Não necessita de kit de linguagem

NC-PF2

Central de Incêndios Convencional, 2 zonas

Especificações técnicas

General

Maximum system capacity (device count)	até 1280
Network size (nodes)	até 32

Electrical

Power supply type	VAC
Power consumption	2 A @ 24 VDC
Operating voltage	110 VAC @ 50 Hz ou 230 VAC @ 50 Hz (+10% -15%) Tipo de cabo: 3 x 1.5 mm² (Fase, neutro, terra)
Current consumption	2 A @ 110/240 VAC 130 mA (alarme, sem dispositivo)(alimentação painel) 50 mA (repouso, sem dispositivos) (alimentação painel)

Loop

Maximum loop capacity	2

Zone

Maximum zone capacity	até 2
Operating voltage	22 VDC (18 to 24 VDC)
Quantity of devices per zone	32 max.
Rating	65 mA (max. Load)
Cable rating	40 ohm (resistência max. de cabo), 500 nF (capacitância max. do cabo)

Input

Input quantity	2
Input type and rating	100 ohm (resistência máx do cabo)

Output

Supervisory voltage	-15 a +28 VDC
Auxilliary power	24 VDC (21 a 28 VDC)
Supervised Outputs	2
Load (max.)	250 mA
Non Supervised Outputs	2
Load	2 A @ 30 VDC

Standby battery

Capacity	2 x 12 V, 7.2 Ah (SLA)

Physical

Form factor	Klein
Physical dimensions	320 x 435 x 134 mm (L x A x P)
Net weight	2.8 kg (sem baterias)
Shipping weight	4.5 kg
Colour	Cinzento (RAL 7035)
Mounting type	Montagem em superfície
Cable entries	Ø 20 mm - 14 / 2 / 12 (top / bottom / rear)

Environmental

Operating temperature	-5 a +50°C
Storage temperature	-20 a +70°C
Relative humidity	10 a 95% sem condensação
Environment	Drinnen
IP rating	IP30

Regulatory

Compliancy	CPD, RoHS, WEEE
Certification	EN54-13, EN54-2, EN54-4

Auxilliary Supply Output

Load (max.)	250 mA @ 25°C / 195 mA @ 40°C

KIDDE COMMERCIAL

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57